



SSM/SSV Series Alarm Bells

System Sensor's SSM and SSV series bells are low current, high decibel notification appliances for use in fire and burglary systems or other signaling applications.



Features

- Approved for indoor and outdoor use
- Low current draw
- High dB output
- Available in six-inch, eight-inch, and ten-inch sizes
- AC and DC models
- DC models polarized for use with supervision circuitry
- Mount directly to standard four-inch square electrical box indoors
- SSM and SSV series pre-wired

Reliable Performance. The SSM and SSV series provide loud resonant tones. The SSM series operates on 24VDC and are motor driven, while the SSV series operates on 120VAC utilizing a vibrating mechanism.

Simplified Installation. For indoor use, the SSM and SSV series mount to a standard four-inch square electrical box. For outdoor applications, weatherproof back box, model number WBB, is used.

The SSM and SSV series come pre-wired, to reduce installation time. The SSM series incorporates a polarized electrical design for use with supervision circuitry.

Agency Listings



SSM/SSV Specifications

Architectural/Engineering Specifications

Model shall be a SSM or SSV Series alarm bell. Bells shall have underdome strikers and operating mechanisms. Gongs on said bells shall be no smaller than nominal 6" / 8" / 10" (specify size) with an operating voltage of 24VDC or 120VAC (specify by part number). Bells shall be suitable for surface or semi-flush mounting. Outdoor surface mounted installations shall be weatherproof (using optional WBB weatherproof electrical box). Otherwise bells shall mount to a standard 4" square electrical box having a maximum projection of 2 1/2". Bells shall be located as shown on the drawings or as determined by the Authority Having Jurisdiction. Bells shall be listed for indoor/outdoor use by Underwriters Laboratories and the California State Fire Marshal, and approved by Factory Mutual and MEA.

Physical/Operating Specifications

Operating Temperature Range	-31°F to 140°F
Operating Voltage	SSM series: 24VDC SSV series: 120VAC
Termination	Provided with 2 sets of leads for in/out wiring
Service Use	Fire Alarm, General Signaling, Burglar Alarm
Warranty	3 years

Electrical Specifications

Model	Gong Diameter (inches)	Nominal Voltage	Operating Voltage Limit	Maximum Current	Sound Output (dBA)
SSM24-6	6	Regulated 24VDC	16 to 33VDC	DC-31.1mA/ FWR-53.5mA	82
SSM24-8	8	Regulated 24VDC	16 to 33VDC	DC-31.1mA/ FWR-53.5mA	80
SSM24-10	10	Regulated 24VDC	16 to 33VDC	DC-31.1mA/ FWR-53.5mA	81
SSV120-6	6	Regulated 120VAC	96 to 132VAC	53mA	85
SSV120-8	8	Regulated 120VAC	96 to 132VAC	53mA	82
SSV120-10	10	Regulated 120VAC	96 to 132VAC	53mA	82

* Sound output measured at Underwriter Laboratories, as specified in UL464

Ordering Information

UL/FM Model No.	ULC/Canadian Model No.	Description
SSM24-6	SSM24-6A	Bell, 6", 24VDC, Polarized, 82dBA
SSM24-8	SSM24-8A	Bell, 8", 24VDC, Polarized, 80dBA
SSM24-10	SSM24-10A	Bell, 10", 24VDC, Polarized, 81dBA
SSV120-6	SSV120-6A	Bell, 6", 120VAC, 85dBA
SSV120-8	SSV120-8A	Bell, 8", 120VAC, 82dBA
SSV120-10	SSV120-10A	Bell, 10", 120VAC, 82dBA
WBB		Weatherproof back box for SSM and SSV series, when installed outdoors



3825 Ohio Avenue • St. Charles, IL 60174
Phone: 800-SENSOR2 • Fax: 630-377-6495

©2007 System Sensor.
Product specifications subject to change without notice. Visit systemsensor.com for current product information, including the latest version of this data sheet.
A05-0260-008 • 4/07 • #1676